

**PARAFUSO COM SEXTAVADO INTERNO - SEM CABEÇA - PONTA CÔNCAVA RECARTEADA
DIN 916 - AÇO LIGA - UNC - TEMPERADO E REVENIDO - OXIDADO OLEADO**

													
Diâmetro* ► / Comprimento* ▼ (POL)													
#4 UNC 40	#5 UNC 40	#6 UNC 32	#8 UNC 32	#10 UNC 24	1/4 UNC 20	5/16 UNC 18	3/8 UNC 16	7/16 UNC 14	1/2 UNC 13	5/8 UNC 11	3/4 UNC 10	7/8 UNC 9	1 UNC 8
1/8	1/8	1/8	1/8										
3/16	3/16	3/16	3/16	3/16	3/16								
1/4	1/4	1/4	1/4	1/4	1/4	1/4	1/4						
5/16	5/16	5/16	5/16	5/16	5/16	5/16	5/16						
3/8	3/8	3/8	3/8	3/8	3/8	3/8	3/8	3/8	3/8				
1/2	1/2	1/2	1/2	1/2	1/2	1/2	1/2	1/2	1/2	1/2			
5/8	5/8	5/8	5/8	5/8	5/8	5/8	5/8	5/8	5/8	5/8	5/8		
	3/4	3/4	3/4	3/4	3/4	3/4	3/4	3/4	3/4	3/4	3/4		
		7/8	7/8	7/8	7/8	7/8	7/8	7/8	7/8	7/8	7/8		
		1	1	1	1	1	1	1	1	1	1	1	1
				1-1/4	1-1/4	1-1/4	1-1/4	1-1/4	1-1/4	1-1/4	1-1/4		
				1-1/2	1-1/2	1-1/2	1-1/2	1-1/2	1-1/2	1-1/2	1-1/2	1-1/2	
					1-3/4	1-3/4	1-3/4	1-3/4	1-3/4	1-3/4	1-3/4		
					2	2	2	2	2	2	2	2	2
							2-1/2	2-1/2	2-1/2	2-1/2	2-1/2	2-1/2	2-1/2
							3		3	3	3	3	3
													4

* Medidas em polegadas.

- Tabela em medidas padrão, consulte-nos para medidas especiais.